EZ LOC® CABLE SEAL 1/16", 3/32" & 1/8"



EZ Loc is a medium-duty cargo security seals featuring non-preformed security cable that frays when cut with various marking options for customized tracking. The EZ Loc 1/16" is approved by the sweetener industry for bulk rail & truck shipments and the 3/32" is preferred by the chemical & food processing industries.



EZ Loc 1/8" is ISO 17712: 2013 High Security seal and C-TPAT Compliant.



APPLICATIONS

- Rail Cars
- Containers
- Hopper Cars
- Tank Cars
- Tanker Trucks
- Truck & Trailer Doors
- · Valves and Meters
- Intermodal Containers

FEATURES

- · Available as a Standard Product
- Features non-preformed security cable that frays when cut
- · Remove with cable cutters
- Pulls tight for maximum security

MATERIAL

- Lock body: corrosion-resistant cast zinc
- Cable: galvanized non-preformed aircraft control cable

STRENGTH CHARACTERISTICS

- 1/16" (1.6mm) Tensile strength: 750 lbs (3.3 kN)
- 3/32" (2.4mm) Tensile strength: 1,000 lbs (4.5 kN)
- 1/8" (3.2mm) Tensile strength: 3,300 lbs (15 kN)

DIMENSIONS

- · Cable diameter:
 - o 1/16" (1.6mm)
 - o 3/32" (2.4mm)
 - o 1/8" (3.2mm)
- Standard cable length: 12" (30.5cm)
 - o Custom lengths available in 2" (5.1cm) increments







EZ LOC® CABLE SEAL 1/16", 3/32" & 1/8"



MARKING/PRINTING

- Standard Marking: Cold Stamped Sequential Numbering
- Minimum quantities apply to customized versions of this product
 please call for details
- Cold Stamped with 2 lines up to 6 characters and 6 digits
- Optional: Ink Jet or Laser with 2 lines up to 8 characters and 6 digits. Barcode available on laser or inkjet
- Laser Tag Serial Number Transfer optional





COLORS

Colors: Mill Finish / Black / Blue / White / Green / Yellow / Orange / Red



PACKAGING

- Packaging
 - o 1/16" (1.6mm) 500/box
 - o 3/32" (2.4mm) 500/box
 - o 1/8" (3.2mm) 250/box
- Box dimensions all items: 16"x 13"x 6" (41cm x 33 cm x 16cm)
- · Weight per Box:
 - o 1/16" (1.6mm): 30 lb (13.6 kg)
 - o 3/32" (2.4mm): 32 lb (14.5 kg)
 - o 1/8" (3.2mm): 26 lb (11.8 kg)

