



FlexSecure FS15

The FlexSecure FS15 is a 1.5 mm (1/16") anodized aluminum bodied cable seal. FS15 is regularly used in bulk food and chemical shipments over the road.

APPLICATIONS

- High Value Shipments
- Trailer Door Latches
- Container Door Latches
- Bulk Tankers
- Valves and Meters
- Railcars

FEATURES

- Tamper-evident cable separates into individual strands when cut and cannot be resealed
- Provides added durability over plastic bodied seals but maintains the color identification
- Provides a versatile method of identification
- Can be customized by laser printing a name, logo, consecutive numbers and barcode

MATERIAL

- Main body: Aluminum alloy
- Internal Locking Components: Zinc and Steel
- Cable: galvanized non-preformed aircraft control cable

STRENGTH CHARACTERISTICS

- Average pull apart strength: 727 lbs. (330kg)

DIMENSIONS

Body: 1.12" x 0.90" x 0.24" (28.6mm x 22.9mm x 6.1mm) Cable Diameter: 1/16" (1.5 mm)
Cable Length: Standard - 12" (30.5 cm) Custom lengths available



FlexSecure FS15

MARKING/PRINTING

- Minimum quantities apply to customized versions of this product – please call for details
- Laser Printing: Name, logo, consecutive numbers, barcode

COLORS

Standard Colors: Red / Blue / Black / Green



PACKAGING

Standard: 10 per tray

200 seals per carton

Box dimensions: 16.5" x 9.5" x 7.25" (41.9cm x 24.1cm x 18.4cm)

Weight: 6.6 lbs. (3kg)

